# SAFETY DATA SHEET

# 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

## 1.1 Product identifier

Product name BLUCEM HS400

HS400

Synonyms

### 1.2 Uses and uses advised against

Uses HIGH STRENGTH THIXOTROPIC PUMPABLE GROUTING

### **1.3 Details of the supplier of the product**

Supplier name	BLUEY TECHNOLOGIES P/L
Address	Lot 8, 53 Metroplex Ave, Murarrie, QLD, 4172, AUSTRALIA
Telephone	(07) 3399 3635
Fax	(07) 3899 9822
Email	bluey@bluey.com.au
Website	http://www.bluey.com.au

### 1.4 Emergency telephone numbers

**Emergency** (07) 3399 3635

# 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

GHS classifications Skin Corrosion/Irritation: Category 2 Serious Eye Damage / Eye Irritation: Category 1 Specific Target Organ Systemic Toxicity (Single Exposure): Category 3

### 2.2 GHS Label elements

Signal word	DANGER	
Pictograms		
Hazard statements		

H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.

### **Prevention statements**

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.



Response statements	
P302 + P352 P304 + P340	IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P321	Specific treatment is advised - see first aid instructions.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before re-use.
Storage statements	
P403 + P233 P405	Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Disposal statements	
P501	Dispose of contents/container in accordance with relevant regulations.
2.3 Other hazards	

No information provided.

# 3. COMPOSITION/ INFORMATION ON INGREDIENTS

### 3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
PORTLAND CEMENT	65997-15-1	266-043-4	>60%
GRADED SAND	14808-60-7	238-878-4	10 to <30%
NON HAZARDOUS INGREDIENTS	Not Available	Not Available	Remainder

# 4. FIRST AID MEASURES

### 4.1 Description of first aid measures

EyeIf in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to<br/>stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.InhalationIf inhaled, remove from contaminated area. Apply artificial respiration if not breathing.

SkinIf skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.<br/>Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

Ingestion For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting. Rinse mouth out with water and give plenty of water to drink.

**First aid facilities** Eye wash facilities should be available.

## 4.2 Most important symptoms and effects, both acute and delayed

Irritating to the eyes, skin and respiratory system. Chronic over exposure to silica quartz dust may result in silicosis (lung disease). Principal symptoms of silicosis are coughing and breathlessness. Some individuals may exhibit an allergic response upon exposure to this product, possibly due to the trace amounts of chromium present. Crystalline silica and hexavalent chromium compounds are classified as carcinogenic to humans (IARC Group 1).

## 4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

# 5. FIRE FIGHTING MEASURES

## 5.1 Extinguishing media

Use an extinguishing agent suitable for the surrounding fire.

## 5.2 Special hazards arising from the substance or mixture

Non flammable. May evolve toxic gases if strongly heated. May evolve carbon oxides and calcium oxides when heated to decomposition. Heating crystalline silica to temperatures above 870°C may result in the formation of tridymite and cristobalite.

# 5.3 Advice for firefighters

Treat as per requirements for surrounding fires. Evacuate area and contact emergency services. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.



### 5.4 Hazchem code

None allocated.

# 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Contact emergency services where appropriate.

### 6.2 Environmental precautions

Prevent product from entering drains and waterways.

### 6.3 Methods of cleaning up

Contain spillage, then collect and place in suitable containers for reuse or disposal. Avoid generating dust.

### 6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

# 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, removed from moisture, incompatible substances and foodstuffs. Ensure packages are adequately labelled, protected from physical damage and sealed when not in use.

### 7.3 Specific end uses

No information provided.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control parameters

### Exposure standards

Ingredient	Reference	TWA		STEL	
ingreatent	Kelerence		mg/m³	ppm	mg/m³
Portland Cement	SWA (AUS)		10		
Quartz (respirable dust)	SWA (AUS)		0.1		

### **Biological limits**

No biological limit values have been entered for this product.

### 8.2 Exposure controls

**Engineering controls** Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain dust levels below the recommended exposure standard.

### PPE

Eye / FaceWear dust-proof goggles.HandsWear PVC or rubber gloves.BodyWhen using large quantities or where heavy contamination is likely, wear coveralls.

**Respiratory** Where an inhalation risk exists, wear a Class P1 (Particulate) respirator. At high dust levels, wear a Powered Air Purifying Respirator (PAPR) with Class P3 (Particulate) filter or a Class P3 (Particulate) respirator.



# ChemAlert.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

	na enerniear prepertiee
Appearance	GREY POWDER
Odour	CEMENT ODOUR
Flammability	NON FLAMMABLE
Flash point	NOT RELEVANT
Boiling point	> 1200°C
Melting point	NOT AVAILABLE
Evaporation rate	NOT AVAILABLE
рН	11 to 12
Vapour density	NOT AVAILABLE
Specific gravity	NOT AVAILABLE
Solubility (water)	SLIGHTLY SOLUBLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT RELEVANT
Lower explosion limit	NOT RELEVANT
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE
9.2 Other information	
Bulk density	1.2 g/cm <sup>3</sup> to 1.6 g/cm <sup>3</sup>
	5 · · · · · · · · · ·

# **10. STABILITY AND REACTIVITY**

### 10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

### 10.2 Chemical stability

Stable under recommended conditions of storage.

### 10.3 Possibility of hazardous reactions

Polymerization will not occur.

### 10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

### 10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), ethanol, acids (e.g. hydrofluoric acid) and interhalogens (e.g. chlorine trifluoride). Water contact may increase product temperature 2°C to 3°C.

### 10.6 Hazardous decomposition products

May evolve carbon oxides and calcium oxides when heated to decomposition.

# 11. TOXICOLOGICAL INFORMATION

## 11.1 Information on toxicological effects

Acute toxicity	Based on available data, the classification criteria are not met.
Skin	Irritating to the skin. Contact with powder or wetted form may result in irritation, rash and dermatitis.
Еуе	Irritating to the eyes. Contact may result in irritation, lacrimation, pain, redness, corneal burns and possible permanent damage.
Sensitisation	Not classified as causing respiratory sensitisation. However, some individuals may exhibit an allergic response upon exposure to cement, possibly due to trace amounts of chromium.
Mutagenicity	Insufficient data available to classify as a mutagen.
Carcinogenicity	Not classified as a carcinogen. This product may contain trace amounts of 'respirable' crystalline silica and hexavalent chromium compounds which are classified as carcinogenic to humans (IARC Group 1). However, there is sufficient information to conclude that the relative risk of lung cancer from exposure to crystalline silica is increased in persons with silicosis. Therefore preventing the onset of silicosis will also reduce the



cancer risk.

**Reproductive** Insufficient data available to classify as a reproductive toxin.

- **STOT single** Irritating to the respiratory system. Over exposure may result in irritation of the nose and throat, with coughing. High level exposure may result in breathing difficulties.
- **STOT repeated exposure** Not classified as causing organ damage from repeated exposure. Repeated exposure to crystalline silica may cause lung fibrosis (silicosis), however due to the low levels of respirable crystalline silica in this product, adverse health effects are not anticipated with normal use.
- Aspiration This product is a solid and aspiration hazards are not expected to occur.

## **12. ECOLOGICAL INFORMATION**

### 12.1 Toxicity

No information provided.

12.2 Persistence and degradability

No information provided.

#### 12.3 Bioaccumulative potential

No information provided.

### 12.4 Mobility in soil

No information provided.

### 12.5 Other adverse effects

No information provided.

# 13. DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

**Waste disposal** Reuse or recycle where possible. Alternatively, ensure product is covered with moist soil to prevent dust generation and dispose of to an approved landfill site. Contact the manufacturer/supplier for additional information (if required).

Legislation Dispose of in accordance with relevant local legislation.

# 14. TRANSPORT INFORMATION

### NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	None allocated.	None allocated.	None allocated.
14.2 Proper Shipping Name	None allocated.	None allocated.	None allocated.
14.3 Transport hazard class	None allocated.	None allocated.	None allocated.
14.4 Packing Group	None allocated.	None allocated.	None allocated.

### 14.5 Environmental hazards

No information provided.

14.6 Special precautions for user

Hazchem code None allocated.

## 15. REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule

A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

# ChemAlert.

Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Classifications Labelling of Chemicals. The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous Substances [NOHSC: 1008(2004)]. Irritant Hazard codes Xi R37/38 Irritating to respiratory system and skin. **Risk phrases** R41 Risk of serious damage to eyes. Safety phrases S2 Keep out of reach of children. S22 Do not breathe dust. S24/25 Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice S26 S36/37/39 Wear suitable protective clothing, gloves and eye/face protection. S38 In case of insufficient ventilation, wear suitable respiratory equipment. S45 In case of accident or if you feel unwell seek medical advice immediately (show the label where possible). AUSTRALIA: AICS (Australian Inventory of Chemical Substances) Inventory listings All components are listed on AICS, or are exempt.

# **16. OTHER INFORMATION**

Additional information

CEMENT CONTACT DERMATITIS: Individuals using wet cement, mortar, grout or concrete could be at risk of developing cement dermatitis. Symptoms of exposure include itchy, tender, swollen, hot, cracked or blistering skin with the potential for sensitisation. The dermatitis is due to the presence of soluble (hexavalent) chromium.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

### PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

### HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.



Abbreviations	ACGIH	American Conference of Governmental Industrial Hygienists			
	CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds			
	CNS	Central Nervous System			
	EC No.	EC No - European Community Number			
	EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous			
	GHS	Goods) Globally Harmonized System			
	GTEPG	Group Text Emergency Procedure Guide			
	IARC	International Agency for Research on Cancer			
	LC50	Lethal Concentration, 50% / Median Lethal Concentration			
	LD50	Lethal Dose, 50% / Median Lethal Dose			
	mg/m <sup>3</sup>	Milligrams per Cubic Metre			
	OEL	Occupational Exposure Limit			
	pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly			
	pri	alkaline).			
	ppm	Parts Per Million			
	STEL	Short-Term Exposure Limit			
	STOT-RE	Specific target organ toxicity (repeated exposure)			
	STOT-SE	Specific target organ toxicity (single exposure)			
	SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons			
	SWA	Safe Work Australia			
	TLV	Threshold Limit Value			
	TWA	Time Weighted Average			
Report status	This document has been compiled by RMT on behalf of the manufacturer, importer o product and serves as their Safety Data Sheet ('SDS').				
	manufacturer, the current sta at the time of	on information concerning the product which has been provided to RMT by the importer or supplier or obtained from third party sources and is believed to represent ate of knowledge as to the appropriate safety and handling precautions for the product f issue. Further clarification regarding any aspect of the product should be obtained he manufacturer, importer or supplier.			
	While RMT ha	as taken all due care to include accurate and up-to-date information in this SDS, it does			
	not provide an no liability for	ny warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts any loss, injury or damage (including consequential loss) which may be suffered or ny person as a consequence of their reliance on the information contained in this SDS.			
Prepared by	5 Ventnor Ave Western Aust	ralia 6005			
	Phone: +61 8 Fax: +61 8 93				
	Email: info@r	mt.com.au			
	Web: www.rm	it.com.au			
		[ End of SDS ]			

